-				
15	DESIG	any	DRAWN BY	DART AEROSPACE LTD VICTORIA INTERNATIONAL AIRPORT, CANADA
	CHECH	KED	APPROVED	DRAWING NO. REV. B
N		KE	A	DSI 9080 SHEET 1 OF 1
	DATE		,	TITLE SCALE
201	97.1	97.10.20		REPLACEMENT TOW RING NTS
	Α		97.09.02	NEW ISSUE
	В		97.10.20	REPLACE D2660 WITH D2707-041

DART SERVICE INSTRUCTION

TO AMEND INSTALLATION DWG D205-634 REV. A & INSTALLATION DWG D204-635 REV. A SUPERCEDED BY REF. STA SH96-88 & STC SR00563NY

D2592 TOW RING AN4-51A BOLT AN960JD416 WASHER D2570 BUSHINGS (2) (PER INSTALLATION DWG)

OR

REPLACED BY


D2707-041 TOW RING AN970-4 WASHER AN960JD1016 WASHER

98/09/17

SEE DZO4-635 REV.B

0205-634 REV. B

D2660 TOW RING AN4-47A BOLT AN960JD416 WASHER D2570 BUSHINGS (2) (PER DSI 9080 REV. A)



IN EARLY MODEL SKIDTUBES:

- 1. DRILL OUT TOW RING HOLE AND CROSSBOLT SPACER TO Ø0.625
- 2. TOUCH UP HOLES WITH ZINC CHROMATE PRIMER
- 3. LINE BORES WITH SIKAFLEX 241 OR EQUIVALENT SEALANT